

POLYVARI ANNELE

03/07/2012 - 14:45:04

Vacuum transfer and discharge of any chemical



ATEX certified by INERIS

In this version the ringed polyvari **is softer and more flexible** by design different.

The barrel is food grade. It meets the requirements of **EN 12115**.

Caractéristiques techniques :

Inner tube:

Crosslinked polyethylene transparent food and agreed BGVV FDA compliant, smooth, thanks to the ellipse driver loaded carbon.

Reinforcement:

High strength synthetic textile and steel spiral embedded in the material.

Siding:

EPDM rubber black with a blue and white longitudinal markings. Resistant to abrasion, weathering and ozone.

Temperature:

Of -35 ° C to +100 ° C

Spécifications techniques :

Pressure resistance (bar): 10

Safety factor: 4

Maximum length (m): 40

Diameter	RC (mm)	Suitable for Vacuum (mmHg)	Weight (Gr / m)
19x31	60	-0.9	650
25x37	80	-0.9	800
32x44	110	-0.9	1100
38x51	140	-0.9	1200
51x67	180	-0.9	1900
63.5x79.5	250	-0.9	2300
75x91	280	-0.9	2800
100x116	360	-0.9	3800

Usual fittings * (male or female) :



The side mounting pipe may be crimped with shells or collar.

The various assemblies are available in **standard or aseptic**.

Any other type of connection on request.

We reserve the right to modify our products and ranges at any time to improve them