

ALI BOAT SPL 10



APPLICATIONS - ADVANTAGES

Sucion and Delivery of all alimentary liquid. Specially made for loading/unloading of all fatty/non fatty products on boats.

HOSE DESCRIPTION



White smooth NBR to FDA - BFR



Textile plies and embedded steel helix can be made without helix.



Use temperature: **from -40°C up to +90°C** for hot water and up to **+130°C** for steam



Black CR. Resistant to abrasion, ozone, atmospherics, animal and vegetal fat, oils, detergents and to all the usual disinfectants

TECHNICAL SPECIFICATIONS

Diameter	Working Pressure (bar)	Possible Depression (mmHg)	Weight (g/m)	RC (mm)
102x124 = 40 M	10	800	6700	700
152x184 = 40M	10	800	1336	1200
203x254 = 20 M	10	800	1845	1600

USUAL COUPLINGS * (male or female)

SMS, DIN, RJT



FLANGES



SYMETRIC



The fitting assembly can be **crimped, with a clamp, with a collar, or expanded (full flow)**. the different ways of assembling are supplied in a standard or aseptic type.

(*) : all the other types of couplings are available on request



ZI DU TALOU – BP 50 148 – F 76200 DIEPPE
 Tel + 33 (0)2 32 14 52 13 - Fax : +33 (0)2 32 14 52 17
www.anfray.fr – flexible@anfray.fr