















# "HALF SYMETRICAL" COUPLINGS



Complies with the NF E 29-572 standard

HALF COUPLINGS WITHOUT LOCK*													
Options : Also supplied in a weld version or for clamping plates	Gas threaded MALE					Threaded FEMALE							
													
DN available (pas GAZ)	15	20	25	32	40	50	65	80	100				
HALF COUPLINGS WITH LOCK*													
Options : Also supplied in a weld version or for clamping plates	Gas threaded MALE		FEMALE (tap.)		RINGED			RINGED REDUITE					
													
DN available (pas GAZ)	15	20	25	32	40	50	65	80	100				
HALF COUPLINGS WITH LOCK WITHOUT EARS *													
Options : Also supplied in a weld version	FEMELLE				GAS (tapped)		MALE (Gas threaded)						
													
DN available (not GAS)	50			65			80			100			
CAPS*													
Options : Also supplied in a lockable version	WITH LOCK					SIMPLE							
													
LOCK (DN)				40	50	65	80	100	150				
SIMPLIFIED (DN)	25	32	40	50	65	80							
DOUBLE JUNCTION WITH LOCK*													
	DIMENSIONS AVAILABLE (inlet/outlet in mm):												
	32/20	32/25	40/20	40/25	40/32	50/20	50/25	50/32	50/40	65/20	65/25	65/32	65/40
	65/50	80/40	80/50	80/65	90/80	100/40	100/50	100/65	100/80	100/90	150/80		
WRENCH													
	SIZES AVAILABLE:												
	20 à 65				50 à 100				50 à 100 (renforcée)				

(\*) MATERIAL AVAILABLE: BRONZE, ALUMINIUM, STAINLESS STEEL, POLYPROPYLENE  
SEALS: NBR, white EPDM, FPM, PTFE  
Complete documentation on request.



ZI DU TALOU – BP 50 148 – F 76200 DIEPPE  
Tel + 33 (0)2 32 14 52 13 - Fax : +33 (0)2 32 14 52 17  
[www.anfray.fr](http://www.anfray.fr) – [flexible@anfray.fr](mailto:flexible@anfray.fr)