





MULTIFFOD B



APPLICATIONS - ADVANTAGES

Suction and discharge of **FOODSTUFFS** (dairy products, sodas, deep-frozen foodstuffs, alcohol up to 96%, animal and vegetal fat) and **COSMETIC** and **PHARMACEUTICAL** industries.




HOSE DESCRIPTION

-  Smooth inner liner, MIRROR-like cover, extruded in white Butyl rubber (FDA approval). Resistant to animal and vegetal fats, as well as oils, detergents and usual disinfectants. Odourless and tasteless. For applications which require the use of aggressive cleaning products.
-  Reinforced by 2 steel wires integrated in the wall and by highly resistant textile plies  Working temperature: **from -40°C up to +120°C**, up to 130°C when in steam phase (open circuit).
-  Blue EPDM rubber external cover, resistant to abrasion, ozone, atmospheric, animal and vegetal fats, oils, detergents and to all usual disinfectants. White longitudinal branding.

TECHNICAL SPECIFICATIONS

Diameter	Working Pressure (bar)	Possible Depression (mmHg)	Weight (g/m)	RC (mm)
19 x 31	10	680	670	80
25 x 37	10	680	870	120
32 x 44	10	680	1030	150
38 x 52	10	680	1470	200
50 x 64	10	680	1820	250
65 x 81	10	680	2810	360
75 x 91	10	680	3170	450
102 x 120	10	680	4460	600

USUAL COUPLINGS * (male or female)

SMS, DIN, RJT	CLAMP	HALF SYMETRICAL
		

The fitting assembly can be **crimped, with a clamp, with a collar, or expanded (full flow)**. the different ways of assembling are supplied in a standard or aseptic type.

(*) : all the other types of couplings are available on request

We reserve the right to modify our products at any moment to improve them.

