

SILIX Clear D ou SD





APPLICATIONS - ADVANTAGES


DELIVERY VERSION D OR SUCION: DELIVERY VERSION SD


Hose specially made for suction/delivery for all utmost pure liquids, food, as well as 96% alcohols. Considering his application in sterile environment. The different materials have been very carefully selected. Hose usually used on process applications. Silicone meeting FDA EP 3.1.9 (European pharmacopeia IV ed), USP Class VI – Non cytotoxic according to ISO 10993. part 5 XXVI ed 2003.

HOSE DESCRIPTION

-  Translucid silicone, food and pharmaceutical quality. Smooth, mirror like, tasteless

-  Polyester plies version D + stainless steel 304L version SD




 Use temperature: from **-60°C up to +180°C**. Steam sterilisation up to **135°C**, hot air up to **180°C** during **30 minutes**.

-  Translucid atoxic silicone for an easy cleaning.

TECHNICAL SPECIFICATIONS

Diameter	Working Pressure (bar)		RC (mm)	Weight (g/m)
10 x 20	18	18	30	420
13 x 23	16	16	40	500
16 x 26	14	15	45	560
19 x 29	13	14	55	620
25 x 35	11	12,5	65	760
32 x 42	10	11	95	920
38 x 48	9,5	10,5	110	1300
50 x 60	8	8	150	1660
65 x 75	7	6,5	180	2020
75 x 97	6	6	240	2700
102 X 114	3,5	4	360	3800

USUAL COUPLINGS * (male or female)

<p>SMS, DIN, RJT</p> 	<p>CLAMP</p> 	<p>WINE</p> 
--	--	---

The fitting assembly can be **crimped, with a clamp, with a collar, or expanded (full flow)**. the different ways of assembling are supplied in a standard or aseptic type.



() : all the other types of couplings are available on request*



ZI DU TALOU – BP 50 148 – F 76200 DIEPPE
Tel + 33 (0)2 32 14 52 13 - Fax : +33 (0)2 32 14 52 17
www.anfray.fr – flexible@anfray.fr