



# SPIRIFLEX



## APPLICATIONS - ADVANTAGES

The vineyard reference.  
Sucion delivery of alcohol products.

## HOSE DESCRIPTION



UPE. Alimentary film to BDVV + FDA tasteless and odourless.



Reinforced by synthetic plies, embedded helix.



Use temperature: from **-30°C** up to **+90°C**; and steam sterilization at **130°C (30 minutes)**.



BLUE EPDM – SMOOTH TO FDA

## TECHNICAL SPECIFICATIONS


Diameter	Working Pressure (bar)	Weight (g/m)	RC (mm)
25 x 36	6°	730	110
32 x 43	6	900	150
38 x 50	6	1360	180
51 x 64	6	1820	220
63,5 x 76,5	6	2580	300
70 x 83	6	2800	360
76 x 90	6	3100	400

## USUAL COUPLINGS \* (male or female)

SMS, DIN, RJT



CLAMP



HALF SYMMETRICAL



The fitting assembly can be **crimped, with a clamp, with a collar, or expanded (full flow)**.  
the different ways of assembling are supplied in a standard or aseptic type.

(\*) : all the other types of couplings are available on request



ZI DU TALOU – BP 50 148 – F 76200 DIEPPE  
Tel + 33 (0)2 32 14 52 13 - Fax : +33 (0)2 32 14 52 17  
[www.anfray.fr](http://www.anfray.fr) – [flexible@anfray.fr](mailto:flexible@anfray.fr)