

VAPALIMENT



APPLICATIONS - ADVANTAGES

THE CLEANING REFERENCE

Steel wire option

Discharge of non-fatty FOODSTUFF containing a maximum of 45% of alcohol, as well as **HOT WATER (+95°C)** and **STEAM (+164°C)**.

HOSE DESCRIPTION



White EPDM. Resistant to detergents and usual disinfectants.



Synthetic plies



Use temperature: **from -40°C up to +95°C** for hot water and up to **+164°C** for steam




Blue elastomer cover, resistant to abrasion, ozone, atmospheric, animal and vegetal fat, oils, detergents and to all the usual disinfectants ..

TECHNICAL SPECIFICATIONS


Diameter	Working Pressure (bar)	Possible Depression in steel wire option (mmHg)	Weight (g/m)	RC (mm)
10 x 20	20 at 95 / 6 at 164	600	270	75
13 x 23	20 at 95 / 6 at 164	600	340	100
16 x 28	20 at 95 / 6 at 164	600	510	120
19 x 31	20 at 95 / 6 at 164	600	590	160
25 x 39	20 at 95 / 6 at 164	600	890	200
32 x 46	20 at 95 / 6 at 164	600	1080	260
38 x 54	20 at 95 / 6 at 164	600	1470	300
50 x 67	20 at 95 / 6 at 164	600	1800	380

USUAL COUPLINGS * (male or female)


SMS, DIN, RJT



CLAMP



WINE



The fitting assembly can be **crimped, with a clamp, with a collar, or expanded (full flow)**. the different ways of assembling are supplied in a standard or aseptic type.

(*) : all the other types of couplings are available on request

We reserved the right to modify our products at any moment to improve them.



ZI DU TALOU – BP 50 148 – F 76200 DIEPPE
Tel + 33 (0)2 32 14 52 13 - Fax : +33 (0)2 32 14 52 17
www.anfray.fr – flexible@anfray.fr